

DMR Material POMC-WD83

Acetal Co-Polymer Engineering Thermoplastic



MATERIAL DATA SHEET (Version 5.0 – 10.2017)

Description

DMR material POMC-WD83 is an industry standard semi crystalline engineering thermoplastic which is commonly referred to as POM, TAL and / or Acetal. It has high mechanical strength, rigidity, excellent wear resistance and good sliding properties. Very low moisture absorption provides this material with good dimensional stability, making POMC-WD83 a highly versatile engineering thermoplastic material which can be used for a wide range of components in multiple industries.

Physical Properties

Property	Test method	Unit	Typical value
Colour			White
Shore Hardness	Shore D	DIN ISO 53505	83
Yield point	ISO 527	MPa	68
Elongation at break	ISO 527	%	30
Tensile Modulus of elasticity	ISO 527	MPa	3.000
Moisture Absorption in air (23°C / 50% RH)	ISO 62	%	0.2
Density	ISO 1183-1	g/cm ³	1.41
Surface resistivity	IEC 60093	Ohm	10 ¹³
Volume resistivity	IEC 60093	Ohm cm	10 ¹³
Melting Point	ISO 11357	°C	165
Heat Deflection Temperature	ISO 75	°C	110
Coefficient Of Linear Thermal Expansion	*	10 ⁻⁶ K ⁻¹	110
Service temperature (Long term)		°C	-50 to +100
Service temperature (short term - max)		°C	+140

* (Average between +20 to +60°C)

Main Characteristics

- High mechanical strength
- High Impact strength
- Good dimensional stability
- Low moisture uptake
- Good wear and sliding properties
- Good electrical insulating properties

Typical products

- Anti-Extrusion / Back-up Rings
- Thrust washers
- Bearing rings / guide rings
- Bushes
- Scraper seals
- Bespoke parts

Typical Applications

Due to its good dimensional stability and low moisture uptake, POMC-WD83 is an excellent material choice for guide rings, bearing rings, bearing bushes, thrust washers, valve seats, scraper rings and back-up rings commonly used in the sealing industry.

Tel: 0044 (0) 114 243 2777 . Fax: 0044 (0) 114 242 2300 . Mail: sales@dmrseals.co.uk . Web: www.dmrseals.co.uk

DMR Seals Ltd believes that the information above is an accurate description of the typical characteristics and/or uses of the product or products, however DMR Seals Ltd makes no warranty, expressed or implied, that parts manufactured from this / and or any other material will perform satisfactorily in the customers application. It is the customers responsibility to thoroughly test products in their specific application to determine performance, efficiency and safety for each end-use product, device or application. The information and data contained herein are based on standard test pieces according to the corresponding ISO, DIN & ASTM standards and cannot be directly related to finished seals, gaskets or other sealing products and should be used only as a general guide.