

# DMR Material FC815

## Mineral Filled PTFE



### MATERIAL DATA SHEET (Version 5.0 – 01.2021)



High Temperature




Chemical resistance



Compressive Strength



FDA Compliant



Wear Resistant

### Description

DMR Seals FC815 material is a white FDA Compliant PTFE which has been reinforced with a mineral filler which provides the material with increased compressive strength and wear resistance.

FC815 PTFE material is commonly used for seals, bushes and wear rings in food industry applications due to its FDA compliance.

### Physical Properties

Property	Test method	Unit	Typical value
Colour			White
Density	ASTM D792	g/cm <sup>3</sup>	2.17-2.25
Hardness	ASTM D2240	Shore D	≥55
Tensile strength (cross direction)	ASTM D4745	N/mm <sup>2</sup>	≥14
Elongation at break	ASTM D4745	%	≥200
Compressive strength (1% deformation)	ASTM D695	N/mm <sup>2</sup>	≥5
Wear factor (PV = 0.7 N/mm <sup>2</sup> ·m/s)	ASTM D3702	µm/h. N/mm <sup>2</sup> .m.min	0.015-0.023
Service temperature *		°C	-200 to +260

\* (Individual testing in application conditions is mandatory)

### Main Characteristics

- Good compressive strength
- Good deformation resistance
- Good chemical resistance
- FDA compliant

### Typical products

- Back-up Rings
- Thrust washers
- Bushes
- Valve seat seals

### Typical Applications

Due to its compliance in food contact applications, good compressive strength, deformation and wear resistance, FC815 is a good material choice for seals and wear rings within the food industry.

Tel: 0044 (0) 114 243 2777 . Fax: 0044 (0) 114 242 2300 . Mail: [sales@dmrseals.co.uk](mailto:sales@dmrseals.co.uk) . Web: [www.dmrseals.co.uk](http://www.dmrseals.co.uk)

DMR Seals Ltd believes that the information above is an accurate description of the typical characteristics and/or uses of the product or products, however DMR Seals Ltd makes no warranty, expressed or implied, that parts manufactured from this / and or any other material will perform satisfactorily in the customers application. It is the customers responsibility to thoroughly test products in their specific application to determine performance, efficiency and safety for each end-use product, device or application. The information and data contained herein are based on standard test pieces according to the corresponding ISO, DIN & ASTM standards and cannot be directly related to finished seals, gaskets or other sealing products and should be used only as a general guide.